

NOTES:


1. MAXIMUM WORKING PRESSURE : 500 PSIG.
2. ALLOWABLE OPERATING TEMPERATURE: -20°F to 300°F.
3. GASKET AND CAUTION TAG TO BE SEALED IN THE PLASTIC BAG AND SHIPPED LOOSE WITH VALVE.

TOLERANCES UNLESS OTHERWISE SPECIFIED
 LINEAR=±.030, ANGULAR=±2°

3RD ANGLE PROJECTION

COMMENTS:

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HENRY TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HENRY TECHNOLOGIES IS PROHIBITED.

NEXT ASSY.:	SIM. TO:
STOCK SIZE:	MATERIAL: CAST BRONZE
SIZE: 1-3/8" O.D.S	WEIGHT: 5.284 LBS
DESCRIPTION:	
CHECK VALVE 1-3/8" ODS	
SHEET: 1 OF 1	 HENRY
SCALE: 1:1	
DRAWN: KD	
DATE: 09/06/2024	
APPROVED:	DRAWING NO./PART NO.:
	205-1-3/8-CUST
	REV:
	-

Other: H:\HENRY\ValveAssy\