



NOTES:

1. MAXIMUM WORKING PRESSURE : 500 PSIG.
2. ALLOWABLE OPERATING TEMPERATURE: -20°F to 300°F.
3. GASKET AND CAUTION TAG TO BE SEALED IN THE PLASTIC BAG AND SHIPPED LOOSE WITH VALVE.
4. UL REGISTERED.

TOLERANCES UNLESS OTHERWISE SPECIFIED
 0.00=±.015, 0.000=±.005, ANG=±0.5°
 63 FINISH ALL OVER REMOVE ALL BURRS



COMMENTS:

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HENRY TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HENRY TECHNOLOGIES IS PROHIBITED.

NEXT ASSY.:	SIM. TO:
STOCK SIZE:	MATERIAL: FORGED BRASS
SIZE:	WEIGHT: 14.72 LBS

DESCRIPTION:
CHECK VALVE

SHEET: 1 OF 1	HENRY [®]	DRAWING NO./PART NO.:	REV:
SCALE: 1:3			
DRAWN: NT	DATE: 9/24/2024		
APPROVED:			

Other: H:\HVSubAssy(8s)\