



NOTES:

1. MAXIMUM WORKING PRESSURE : 500 PSIG.
2. ALLOWABLE OPERATING TEMPERATURE: -20°F to 300°F.
3. GASKET AND CAUTION TAG TO BE SEALED IN THE PLASTIC BAG AND SHIPPED LOOSE WITH VALVE.
4. UL REGISTERED.

TOLERANCES UNLESS OTHERWISE SPECIFIED
 0.00=±.015, 0.000=±.005, ANG=±0.5°
 63 FINISH ALL OVER REMOVE ALL BURRS

3RD ANGLE PROJECTION

COMMENTS:

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HENRY TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HENRY TECHNOLOGIES IS PROHIBITED.

NEXT ASSY.:	SIM. TO:
STOCK SIZE:	MATERIAL: CAST BRONZE
SIZE:	WEIGHT: 23.05 LBS

DESCRIPTION:
CHECK VALVE

SHEET: 1 OF 1		DRAWING NO./PART NO.:	REV:
SCALE: 1:3			
DRAWN: NT	DRAWING NO./PART NO.:		REV:
DATE: 9/25/2024	205-2-5/8-CUST		
APPROVED:			-

Other: H:\HENRY\ValveAssy\